

Multipurpose epoxy based solvent putty

# Chem EpoFloor Putty®



## Description

**Chem EpoFloor Putty®** is high build multipurpose three-part solvent free epoxy putty.

## Advantages

- Great Abrasion on surface.
- No odor: applied in food industries.
- Can provide excellent slip properties.

## USES

**Chem EpoFloor Putty®** is ideal to be used for Concrete fairing coat for walls, floors and can be used as repairing agent.

## Coverage

- Approximately 1m<sup>2</sup>/Kg.

## Packaging

**Chem EpoFloor Putty®** is supplied in:

- 5 kg packs
- (Base 2.1/Kg - Hardener 0.4/Kg - Filler 2.5/kg).

## Technical Properties

Phase	Paste
Colour	upon the request
Density	1.68 kg/L + 0.05
Pot life	60 min.
Touches dry	Touch dry
Hard dry of service	24 hour
Full cure	7 days
Working temperature	From 10 to 35 C

## Standards Compliance

- manufacture internal standard.

## Application Instructions

### Preparation:

- All surfaces should be clean, dry and free from contamination.

### Mixing:

**Chem EpoFloor Putty®** is a three component material paste filler, base and hardener, which must be mixed together prior to use.

- Stir the base; continue stirring whilst adding all the contents of the hardener and mix until homogeneous then add filler.

Multipurpose epoxy based solvent putty

# Chem EpoFloor Putty®



## Application:

- **Chem EpoFloor Putty®** it can be applied by good quality steel or wooden tools. Can be applied up till 3 mm thickness in one go.

## Shelf Life

Shelf life is up to 12 months when stored as per recommendations.

## Warehouse Conditions

**Chem EpoFloor Putty®** store in normal temperature and closed shaded dry area in undamaged original packing.

## Technical support

For any technical support, please contact IChem technical office or representatives.

## Quality

All products manufactured by iChemEG, or imported from iChemEG affiliate companies worldwide, are manufactured to procedures certified to conform to the quality, environment, health & safety management systems.

## Health & safety

- **Chem EpoFloor Putty®** is flammable or health hazard material.
- Spillages should be washed down immediately with cold water.
- PPE in accordance with the health and safety rules should be used during the materials application.
- For irritant effects of the non-cured material, avoid contact with skin and eyes during storage and application.
- If the contamination occurs, wash the contaminated part by soap and plenty of water. Urgently contact to nearest hospital.
- Food and drink should be kept outside the application areas and should be kept in closed area
- Residues of material must be removed according to local regulations.
- Fully cured material can be disposed of as household waste under agreement with the responsible local authorities.

Technical Data Sheet - January 2024, Version 1.1.5

Office : 22 El-Shaheed Mohamed Abd  
El-Hadi Street, Nasr City, Cairo  
Website : [www.iChemEg.com](http://www.iChemEg.com)  
Email : [info@ichemeg.com](mailto:info@ichemeg.com)

